


AMENDMENT OF SOLICITATION/MODIFICATION OF CONTRACT		1. CONTRACT ID CODE	
2. AMENDMENT/MODIFICATION NO. 01	3. EFFECTIVE DATE 09/10/2009	4. REQUISITION/PURCHASE REQ. NO. CG 090022	5. PROJECT NO. (If applicable)
6. ISSUED BY AOC - Procurement Division 2nd & D Streets, SW Room H2-263 WASHINGTON, DC 20515		7. ADMINISTERED BY (If other than Item 6)	
8. NAME AND ADDRESS OF CONTRACTOR (No., street, country, state and ZIP Code)		(X) 9A. AMENDMENT OF SOLICITATION NO. RFP090080 X 9B. DATED (SEE ITEM 11) 08/26/2009 10A. MODIFICATION OF CONTRACT/ORDER NO. 10B. DATED (SEE ITEM 11)	
CODE	FACILITY CODE		
11. THIS ITEM ONLY APPLIES TO AMENDMENTS OF SOLICITATIONS			
<input checked="" type="checkbox"/> The above numbered solicitation is amended as set forth in item 14. The hour and date specified for receipt of Offers <input type="checkbox"/> is extended, <input checked="" type="checkbox"/> is not extended.			
Offers must acknowledge receipt of this amendment prior to the hour and date specified in the solicitation or as amended, by one of the following methods: (a) By completing items 8 and 15, and returning ___1___ copies of the amendment; (b) By acknowledging receipt of this amendment on each copy of the offer submitted; or (c) By separate letter or telegram which includes a reference to the solicitation and amendment numbers. FAILURE OF YOUR ACKNOWLEDGMENT TO BE RECEIVED AT THE PLACE DESIGNATED FOR THE RECEIPT OF OFFERS PRIOR TO THE HOUR AND DATE SPECIFIED MAY RESULT IN REJECTION OF YOUR OFFER. If by virtue of this amendment your desire to change an offer already submitted, such change may be made by telegram or letter, provided each telegram or letter makes reference to the solicitation and this amendment, and is received prior to the opening hour and date specified.			
12. ACCOUNTING AND APPROPRIATION DATA (If required)			
13. THIS ITEM ONLY APPLIES TO MODIFICATION OF CONTRACTS/ORDERS.			
IT MODIFIES THE CONTRACT/ORDER NO. AS DESCRIBED IN ITEM 14.			
CHECK ONE	A. THIS CHANGE ORDER IS ISSUED PURSUANT TO: (Specify authority) THE CHANGES SET FORTH IN ITEM 14 ARE MADE IN THE CONTRACT ORDER NO. IN ITEM 10A.		
	B. THE ABOVE NUMBERED CONTRACT/ORDER IS MODIFIED TO REFLECT THE ADMINISTRATIVE CHANGES (such as changes in paying office, appropriation date, etc.) SET FORTH IN ITEM 14, PURSUANT TO THE AUTHORITY OF FAR 43.103(b).		
	C. THIS SUPPLEMENTAL AGREEMENT IS ENTERED INTO PURSUANT TO AUTHORITY OF:		
	D. OTHER (Specify type of modification and authority)		
E. IMPORTANT: Contractor <input type="checkbox"/> is not, <input type="checkbox"/> is required to sign this document and return _____ copies to the issuing office.			
14. DESCRIPTION OF AMENDMENT/MODIFICATION (Organized by UCF section headings, including solicitation/contract subject matter where feasible.)			
This Amendment is issued as follows: 1) Remove page 02511-2 and replace with new page 0211-2 in the Bituminous Concrete for Street Paving Specifications. 2) All other terms and conditions remain the same.			
Except as provided herein, all terms and conditions of the document referenced in Item 9A or 10A, as heretofore changed, remains unchanged and in full force and effect.			
15A. NAME AND TITLE OF SIGNER (Type or print)		16A. NAME AND TITLE OF CONTRACTING OFFICER (Type or print)	
		Lauren Wilson Contracting Officer	
15B. CONTRACTOR/OFFEROR	15C. DATE SIGNED	16B. UNITED STATES OF AMERICA	16C. DATE SIGNED
(Signature of person authorized to sign)		By  (Signature of Contracting Officer)	9/10/09
NSN 7540-01-152-8070 Previous edition unusable		STANDARD FORM 30 (REV. 10-83) Prescribed by GSA FAR (48 CFR) 53.243	

RFP090080

2.01 MATERIALS:

- A. **General:** Use locally available materials and gradations which exhibit a satisfactory record of previous installations.
- B. **Asphalt Leveling Course (over existing pavement):** D.C. "surface C" or binder.
- C. **Fine Aggregates:** Fine aggregates complying with AASHTO "Fine Aggregate for Bituminous Paving Mixtures", M29, and DHSS paragraph 804.02. (A).
- D. **Surface Course Aggregate:** Hot Asphaltic Concrete (Superpave 9.5 Surface Course) shall be compacted to not less than 96 percent of the bulk density of a standard specimen compacted as prescribed in AASHTO T 166 or not less than 92 percent of the maximum specific gravity determined in accordance with AASHTO T 209. Grading requirements for coarse aggregates shall follow DDOT specifications for 9.5 MM, per Table 803.02-1 in DDOT Specifications.
- E. **Tack Coat:** Emulsified asphalt conforming to requirements of AASHTO M140, Grades SS-1, SS-1h, RS-1, or as specified.

2.02 ASPHALT-AGGREGATE MIXTURE:

- A. **Provide plant-mixed,** hot-laid asphalt-aggregate mixture complying with DHSS paragraph 805.01, Table II, Hot Asphalt Concrete Surface (Class C Surface Mixture), within limits specified below and in approved job mix formula:

AGGREGATE

Sieve designation	Percentages by weight passing Square mesh sieve
1/2 inch:	100%
3/8 inch:	85-100%
No. 4:	55-80%
No. 10:	40-65%
No. 40:	10-30%
No. 80:	3-15%
No. 200:	2-8%

- B. **Asphalt Cement:** Percentage of total mixture: As approved for job mix formula by D.C. Department of Public Works.

PART 3 - EXECUTION

3.01 SURFACE PREPARATION:

- A. **Protection of Trees:** Adequate protection shall be provided for trees adjacent to the work sites.
- B. **Protection of existing Sidewalk:** If an existing sidewalk abuts the work site, then care shall be taken not get any asphaltic compounds on the sidewalk, thus causing stains.